

**ILLUMINATION DEVICE; AND COORDINATE MEASURING  
INSTRUMENT HAVING AN ILLUMINATION DEVICE**

**CROSS REFERENCE TO RELATED APPLICATIONS**

This invention claims priority of a German patent application DE 100 31  
5 719.7 which is incorporated by reference herein.

**FIELD OF THE INVENTION**

The invention concerns an illumination device having the features  
of the preamble of independent Claim 1. The invention further concerns a  
coordinate measuring instrument having an illumination device, having the  
10 features of the preamble of independent Claim 5. The dependent claims recite  
advantageous embodiments.

**BACKGROUND OF THE INVENTION**

In the production of semiconductor chips, as packing density  
continually increases the widths of the individual features become ever smaller.  
15 Corresponding to these smaller and smaller structures, requirements are becoming  
more stringent in terms of the specifications of coordinate measuring instruments  
that are used as measurement and inspection systems for measuring feature edges  
and feature positions, and for measuring feature widths. Optical sensing methods  
are still favored for these coordinate measuring instruments, even though feature

widths are already smaller than the light wavelength used for measurement and inspection. The reason is that measurement systems with optical sensing methods are substantially easier to use than systems with other sensing methods, for example using electron beams.

- 5 Because the features being measured are becoming smaller and smaller, however, the requirements in terms of optical system performance, especially resolving power, become more stringent. For example, to allow optically reproducible measurement of feature widths, edge profiles, or the like, the measurement fields must be illuminated as homogeneously as possible.
- 10 Illumination devices that operate with an optical waveguide to generate a homogeneous illumination field are known. One such illumination device is used, for example, in the Leica® LMS IPRO coordinate measurement instrument of Leica Microsystems AG.

In this illumination device, the light of a light source is picked off via a coupling-  
15 in optical system with a small numerical aperture (e.g.  $NA = 0.18$ ) and coupled into a multimode optical waveguide. The light source used is a 100 W Hg-Xe discharge lamp. The multimode optical waveguide possesses a small core diameter of 0.4 mm and a nominal numerical aperture  $NA = 0.21$ . The specimen is then Köhler-illuminated in known fashion via a coupling-out optical system, using  
20 a tube lens and a PLAN-APO 50X objective. An image field with a diameter of 0.056 mm is illuminated with this illumination device. To achieve uniform illumination with inhomogeneities of approximately a few percent in this context,

only a small numerical aperture  $NA = 0.12$  is picked off by the multimode fiber. This corresponds to a semiangle of approx.  $7^\circ$ . As a result, only that region of the fiber's emission characteristic curve in which the intensity of the light varies by only a few percent as a function of emission angle is used.

- 5 The known illumination device has the advantage that the light source, which at the same time is a strong heat source, can be arranged well outside the actual measurement location and at a great distance from the specimen being measured. Temperature influences on the measurement accuracy of the coordinate measuring instrument are thereby minimized. At the same time, the illuminating light is
- 10 conveyed via the flexible optical waveguide to any desired measurement location.

The disadvantage of the known illuminating device is that because of the emission characteristic curve of multimode fibers, the angular region in which the intensity of the emitted light varies only on the order of a few percent is very narrow. If larger fields nevertheless need to be homogeneously illuminated, the fiber

15 diameter must be correspondingly large. The rigidity of optical fibers rises sharply with increasing diameter. For future coordinate measuring instruments, for example, a homogeneously illuminated image field of 0.35 mm is necessary. This would require the use of an optical fiber having a core diameter greater than 1 mm in order to achieve sufficient homogeneity in the image field. Fibers with a core

20 diameter greater than 1 mm are, however, no longer practically usable because of their rigidity.

## SUMMARY OF THE INVENTION

It is therefore the object of the present invention to describe an illumination device for a coordinate measuring instrument for homogeneous illumination of a much larger image field than hitherto possible, in which  
5 simultaneously only a minor light loss is to occur. Brightness differences in the illuminated image field are also intended to be very small.

This object is achieved by an illumination device having a light source, an optical waveguide, a coupling-in optical system which couples the light of the light source into a first end of the optical waveguide, a coupling-out optical system  
10 which couples out the light emerging from a second end of the optical waveguide, and an illuminating optical system which receives the light emerging from the coupling-out optical system and illuminates an image field; in which, according to the present invention:

- 15 a) an optical fiber bundle is arranged as the optical waveguide; and in which
  - b) there is arranged between the coupling-out optical system and the illuminating optical system a homogenizing optical system which homogenizes the nonuniform intensity distribution in the image field of the light emerging from the optical fiber bundle (4).
- 20 Advantageous embodiments of the invention are the subject matter of the dependent claims.

The illumination device according to the present invention in turn uses an optical waveguide. The light of a light source is picked off via an enlarging coupling-in optical system with the largest possible numerical entrance aperture (e.g.  $NA = 0.60$ ) and coupled into the optical waveguide. This already constitutes a difference  
5 from the known illumination device, in which the light of the light source was picked off and coupled into the optical waveguide via a coupling-in optical system with a small aperture. Since the largest possible angle of the brightest portion of the lamp is picked off in the illumination device according to the present invention, a definite gain in intensity is achieved.

10 But in order to eliminate the need to use an optical fiber, i.e. an optical waveguide, having a large core diameter, a fiber bundle is used instead. According to the present invention, the light emitted from the fiber bundle, which usually has an unsatisfactory intensity distribution, is transformed with a homogenizing optical system into a so-called "flat-top" (or "super-Gaussian") distribution.

15 Refractive lens arrays, holographic optical elements (HOEs), diffractive optical elements (DOEs), honeycomb condensers, or combinations of lens arrays and diffusion disks can be used as homogenizing optical systems.

The optimum solution for the homogenizing optical system has proven, however, to be a successive arrangement of a micro-honeycomb condenser and a lens  
20 member. The micro-honeycomb condenser comprises two quartz plates cemented to one another, each of which has on the external surfaces a dense array of planoconvex microlenses, the two external surfaces being reciprocally located in

the focal plane of the microlenses on the respective opposite external surface.

Homogeneity approaches an optimum as the number of transilluminated microlenses increases. This optimum homogeneity of the brightness in the image field is not appreciably improved by any further increase in the number of

5 microlenses.

A further object of the invention is to describe a coordinate measuring instrument having an illumination device for homogeneous illumination of a much larger image field than heretofore possible; at the same time, only a small light loss is to occur. The brightness differences in the illuminated image field are intended to be  
10 very small.

This object is achieved by a coordinate measuring instrument having a horizontally X-Y displaceable measurement stage for receiving a substrate with a feature that is to be measured; having an illumination system with a light source, an optical waveguide, a coupling-in optical system before the optical waveguide, a  
15 coupling-out optical system after the optical waveguide, and an illuminating optical system for illuminating an image field; and having a detector device for determining the position of the feature, in which, according to the present invention,

- a) an optical fiber bundle is arranged as the optical waveguide; and in  
20 which
- b) there is arranged between the coupling-out optical system and the illuminating optical system a homogenizing optical system which

homogenizes the nonuniform intensity distribution in the image field of the light emerging from the optical fiber bundle.

Advantageous embodiments of the invention are the subject matter of the dependent claims.

- 5 Since the intensity distribution of the light emitted from the light guide has, to a good approximation, no further influence on the intensity profile in the image field because of the use according to the present invention of a homogenizing optical system, it is also possible to use, instead of one individual fiber with a large core diameter, a fiber bundle comprising many individual fibers. This type
- 10 of light guide has low rigidity even when its diameter is large. In the case of individual fibers, the emission characteristic curve is strongly dependent on the curvature state of the fiber, which requires more alignment effort. Fiber bundles, on the other hand, are much less sensitive in terms of curvature. The light balance (i.e. the quotient of the total intensity in the image field and the intensity of the
- 15 light emitted by the fiber) is comparatively most favorable in the context of homogenization by means of a lens array.

With an illumination device according to the present invention, a homogeneously illuminated image field with a minimum diameter of 0.35 mm is achieved at a numerical aperture of 0.60. The illumination inhomogeneity is less than  $\pm 2\%$  of

20 the average between the maximum intensity and minimum intensity.

The homogeneously illuminated image field is thus equally large in a coordinate measuring instrument according to the present invention with which features of

semiconductor industry lithography masks can be measured. As a result, for example, it is no longer necessary to refocus in response to changes in the position of feature planes that occur because of production-related mask thickness tolerances. Here again, the illumination inhomogeneity is less than  $\pm 2\%$  of the average between the maximum intensity and minimum intensity. This yields a definite improvement in measurement accuracy, in particular with large masks.

### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be explained in more detail with reference to several exemplary embodiments, with the aid of the schematic drawings in which:

- 10 FIG. 1 shows the optical diagram of an illumination device for a transmitted-light illumination system;
- FIG. 2 shows an enlargement of detail "X" of FIG. 1, i.e. a section through a honeycomb condenser;
- 15 FIG. 3 shows the optical diagram of an illumination device for an incident-light illumination system;
- FIG. 4 shows a coordinating measuring instrument having a combined incident-light and transmitted-light illumination system which comprises a transmitted-light illumination device according to the present invention;
- 20 FIG. 5 shows a schematic beam path before and after the condenser of the transmitted-light illumination device of FIG. 4, for masks of different thicknesses.



In the Figures, similar elements are labeled with the same reference numbers.

## DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 shows the optical diagram of an illumination device according to the present invention, in this case specifically for a transmitted-light illumination system such as can be used, for example, in a coordinate measuring instrument or a stepper.

A transmitted-light illuminating beam path having an optical axis 2 proceeds from a light source 1. The light of light source 1 is picked off via an enlarging coupling-in optical system 3 having the largest possible numerical entrance aperture (e.g. NA = 0.60) and coupled into an optical waveguide. An optical fiber bundle 4 is used as the optical waveguide.

A coupling-out optical system 5, which preferably is configured as an achromat, collimates the light emitted from fiber bundle 4, the inhomogeneous intensity distribution of the light emitted from fiber bundle 4 being retained. As it exits from coupling-out optical system 5 the collimated light is therefore, according to the present invention, directed onto a homogenizing optical system 6 which transforms the inhomogeneous intensity distribution into a so-called "flat-top" (or "super-Gaussian") distribution.

Homogenizing optical system 6 comprises, in this exemplary embodiment, a micro-honeycomb condenser 7 and a lens member 8 which superimpose exit

opening 9 of fiber bundle 4 in an intermediate image plane 10 to form a homogeneous intermediate image.

FIG. 2 shows a detailed enlargement of the region labeled "X" in FIG. 1, depicting a section through a micro-honeycomb condenser 7. The front external surface 11 of micro-honeycomb condenser 7 (at left in FIG. 1) is located in the focal plane of coupling-out optical system 5.

Micro-honeycomb condenser 7 comprises a first planar quartz plate 11 and a second planar quartz plate 12 that are cemented to one another. Cemented surface 14 between first quartz plate 11 and second quartz plate 12 is depicted as being disproportionately thick.

External surface 13 of first quartz plate 11 constitutes the front side of micro-honeycomb condenser 7, onto which the light coming from coupling-out optical system 5 is incident. External surface 15 of second quartz plate 12 constitutes the rear side of micro-honeycomb condenser 7, through which the light emerges again.

Planoconvex microlenses (positive lenses) 16 are etched in a hexagonal arrangement into external surface 13 of first quartz plate 11 and external surface 15 of second quartz plate 12. The etching can be accomplished, for example, with a lithographic process. The two external surfaces 13 and 15 are reciprocally located at the respective focus of microlenses 16 arranged on the respectively opposite external surface 13, 15.

The result is that multiple images of exit opening 9 of fiber bundle 4 are obtained on the rear surface of micro-honeycomb condenser 7. The number of multiple images corresponds to the number of transilluminated microlenses 16. The size of the multiple images is determined by the focal length ratio of achromat 5 and the  
5 focal lengths of microlenses 16.

FIG. 1 shows the continuation of the beam path. Lens member 8, which preferably is configured as an achromat, then images the cross sections of microlenses 16 on front external surface 13 of micro-honeycomb condenser 7 into an intermediate image plane 10 in superimposed fashion. If a sufficiently large number of  
10 microlenses 16 was selected, this superimposition ensures a very homogeneous intermediate image.

The homogenized intermediate image is then, using a condenser 17 that is arranged as an illuminating optical system 17, imaged at reduced size onto a transmitted-light specimen 18. At the same time, the exit surface of micro-  
15 honeycomb condenser 16 is imaged at infinity by condenser 17. The desired homogeneous illumination of the specimen field on transmitted-light specimen 18 is thereby obtained. Transmitted-light specimen 18 can be, for example, the measurement field of a coordinate measuring instrument, or a preparation on a microscope stage.

20 FIG. 3 shows the optical diagram of an illumination device according to the present invention, in this case specifically for an incident-light illumination

system such as can be used, for example, in a coordinate measuring instrument or a stepper.

An incident-light illuminating beam path having an optical axis 2 proceeds from a light source 1. The light of light source 1 is picked off via an enlarging coupling-  
5 in optical system 3 having the largest possible numerical entrance aperture (e.g. NA = 0.60) and coupled into an optical waveguide. An optical fiber bundle 4 is used as the optical waveguide.

The light emitted from fiber bundle 4 is first collimated using a coupling-out optical system 5 which preferably is configured as an achromat. The  
10 inhomogeneous intensity distribution of the light emitted from fiber bundle 4 is retained. As it exits from coupling-out optical system 5 the collimated light is therefore, according to the present invention, directed onto a micro-honeycomb condenser 7 that is part of a homogenizing optical system 6 which transforms the inhomogeneous intensity distribution into a so-called "flat-top" (or "super-  
15 Gaussian") distribution.

As already described, multiple images of the light source (i.e., in the present case, exit opening 9 of fiber bundle 4) are obtained on the rear surface of micro-honeycomb condenser 7. The number of multiple images corresponds to the number of transilluminated microlenses 16.

20 A lens member 8, which preferably is configured as an achromat, then images the cross sections of microlenses 16 on front external surface 13 of micro-honeycomb

condenser 7 into an intermediate image plane 10 in superimposed fashion. If a sufficiently large number of microlenses 16 was selected, this superimposition ensures a homogeneous intermediate image.

The homogenized intermediate image is then imaged at reduced size onto an  
5 incident-light specimen 22 using a lens group 19 and an objective 20 arranged as an illuminating optical system, between which a beam splitter 21 is arranged; and the rear side of micro-honeycomb condenser 15, functioning as a pupil, is imaged at infinity in the specimen space. The desired homogeneous illumination of the specimen field on incident-light specimen 22 is thereby obtained. Incident-light  
10 specimen 22 can be, for example, a measurement field of a coordinate measuring instrument, or a preparation on a microscope stage.

FIG. 4 shows an exemplary embodiment of a coordinate measuring instrument having a combined incident-light and transmitted-light illumination system which comprises a transmitted-light illumination device according to the present  
15 invention.

The coordinate measuring instrument that is depicted has a granite block 23 that is mounted on vibration dampers 24, 25. A measurement stage 26, configured as a frame, is slidingly displaceable on granite block 23 in the X and Y directions (indicated in the drawing by two arrows) on air bearings 27, 28. The frame of  
20 measurement stage 26 is advantageously made of a glass ceramic having a low coefficient of thermal expansion. The drive elements for moving measurement

stage 26 are not depicted. The position of measurement stage 26 is measured in the X and Y directions with a laser interferometer system 29.

A mask 30 is set into the frame of measurement stage 26. Mask 30 is made, for example, of quartz glass. Features 31 are applied on the mask surface. Since

5 measurement stage 26 is configured as a frame, mask 30 can also be transilluminated from below.

Located above mask 30, as the imaging system, is an objective 20 of high optical quality that is adjustable in the Z direction along its optical axis 2 for focusing. By way of a splitter mirror 32, on the one hand the light of an incident-light light  
10 source 33 is introduced into the optical beam path, and on the other hand the imaging rays are directed onto a detector device 34. Detector device 34 is, for example, a CCD camera with a high-resolution pixel array. Incident-light light source 33 emits, for example, in the near UV spectral region. By means of detector device 34, the position of a feature 31 is determined as coordinates on  
15 mask 30.

A transmitted-light illumination device having an adjustable-height condenser 17 and a light source 1 is set into granite block 23 as a further illumination device. A transmitted-light illuminating beam path having an optical axis 2 proceeds from light source 1. The light of light source 1 is picked off via an enlarging coupling-  
20 in optical system 3 having the largest possible numerical entrance aperture (e.g.  $NA = 0.60$ ). A particularly large amount of light of the light source is picked off in this fashion, but the light exhibits particularly large intensity inhomogeneities over

this large aperture. The picked-off light is coupled into an optical waveguide using coupling-in optical system 3. An optical fiber bundle 4 is used as the optical waveguide.

A coupling-out optical system 5, which preferably is configured as an achromat, collimates the light emitted from fiber bundle 4. The inhomogeneous intensity distribution of the light emitted from fiber bundle 4 is retained. As it exits from coupling-out optical system 5 the collimated light is therefore, according to the present invention, directed onto a homogenizing optical system 6 which transforms the inhomogeneous intensity distribution into a so-called "flat-top" (or "super-Gaussian") distribution.

In this exemplary embodiment, homogenizing optical system 6 comprises a micro-honeycomb condenser 7 and a lens member 8 which superimpose exit opening 9 of fiber bundle 4 in an intermediate image plane 10 to form a homogeneous intermediate image. With this embodiment of the homogenizing optical system, even severe intensity differences that occur as a result of the large numerical aperture of the coupling-in optical system can be very effectively homogenized. The residual illumination homogeneity is only less than  $\pm 2\%$  of the average between the maximum intensity and minimum intensity. This results in a definite improvement in the measurement accuracy of the coordinates of features 31, especially with large masks 30.

The optical axis of condenser 17 aligns with optical axis 2 of objective 20.

Adjusting the height of condenser 17 serves to adapt the illuminating rays to be

directed onto feature 31 to different optical thicknesses of masks 30. In particular, the condenser head can extend into the open part of the measurement stage frame. For protection against damage in the context of displacements of measurement stage 36 over the entire mask surface, however, condenser 26 can also be pulled  
5 below the surface of granite block 23. Light sources 1 and 33 can be switched on independently of one another.

FIG. 5 shows the schematic beam path before and after the condenser of the transmitted-light illumination system of the coordinate measuring instrument, in particular for masks of different thicknesses. Condenser 7 with an optical axis 2 is  
10 shown. Intermediate image plane 10 is indicated for orientation.

Condenser 17 is moved in close to a mask 30 that is mounted on the open frame of a measurement stage 26. Mask 30 has features 31 on upper side 35 facing away from condenser 17. This upper side 35 of mask 30 is illuminated with a specific image field having a very homogeneous light intensity. The homogeneously  
15 illuminated image field has, for example, a minimum diameter of 0.35 mm at a numerical aperture of 0.60.

Also indicated, with dashed lines, is a thicker mask 30' having an upper side 35'. Its upper side 35' is considerably farther away from the condenser. Since the illumination device achieves very large homogeneous image fields, even with the  
20 thicker mask 30' the image field is still sufficient for a measurement for the position of upper side 35' which determines the location of the feature planes. As a result, there is no need for refocusing due to changes in the position of the feature



planes which occur as a consequence of production-related thickness tolerances of the masks.

The present invention was described with reference to exemplary embodiments. It is nevertheless apparent to any person skilled in this art that changes and  
5 modifications can be made without thereby leaving the range of protection of the claims recited hereinafter. In particular, the illumination device according to the present invention can be used for any type of measurement or inspection system, microscopes, steppers, etc.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

## PARTS LIST

- 1 Light source
- 2 Optical axis
- 3 Coupling-in optical system
- 4 Optical fiber bundle
- 5 Coupling-out optical system
- 6 Homogenizing optical system
- 7 Micro-honeycomb condenser
- 8 Lens member
- 9 Exit opening of fiber bundle 4
- 10 Intermediate image plane
- 11 First quartz plate
- 12 Second quartz plate
- 13 Front external surface of micro-honeycomb condenser 6
- 14 Cemented surface
- 15 Rear external surface of micro-honeycomb condenser 6
- 16 Microlenses
- 17 Condenser
- 18 Transmitted-light specimen
- 19 Lens group
- 20 Objective
- 21 Beam splitter
- 22 Incident-light specimen
- 23 Granite block
- 24 Vibration damper
- 25 Vibration damper
- 26 Measurement stage
- 27 Air bearing
- 28 Air bearing

- |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 1975a | 1975b | 1975c | 1975d | 1975e | 1975f | 1975g | 1975h | 1975i | 1975j | 1975k | 1975l | 1975m | 1975n | 1975o | 1975p | 1975q | 1975r | 1975s | 1975t | 1975u | 1975v | 1975w | 1975x | 1975y | 1975z |
| 1976a | 1976b | 1976c | 1976d | 1976e | 1976f | 1976g | 1976h | 1976i | 1976j | 1976k | 1976l | 1976m | 1976n | 1976o | 1976p | 1976q | 1976r | 1976s | 1976t | 1976u | 1976v | 1976w | 1976x | 1976y | 1976z |
| 1977a | 1977b | 1977c | 1977d | 1977e | 1977f | 1977g | 1977h | 1977i | 1977j | 1977k | 1977l | 1977m | 1977n | 1977o | 1977p | 1977q | 1977r | 1977s | 1977t | 1977u | 1977v | 1977w | 1977x | 1977y | 1977z |
| 1978a | 1978b | 1978c | 1978d | 1978e | 1978f | 1978g | 1978h | 1978i | 1978j | 1978k | 1978l | 1978m | 1978n | 1978o | 1978p | 1978q | 1978r | 1978s | 1978t | 1978u | 1978v | 1978w | 1978x | 1978y | 1978z |
| 1979a | 1979b | 1979c | 1979d | 1979e | 1979f | 1979g | 1979h | 1979i | 1979j | 1979k | 1979l | 1979m | 1979n | 1979o | 1979p | 1979q | 1979r | 1979s | 1979t | 1979u | 1979v | 1979w | 1979x | 1979y | 1979z |
| 1980a | 1980b | 1980c | 1980d | 1980e | 1980f | 1980g | 1980h | 1980i | 1980j | 1980k | 1980l | 1980m | 1980n | 1980o | 1980p | 1980q | 1980r | 1980s | 1980t | 1980u | 1980v | 1980w | 1980x | 1980y | 1980z |
| 1981a | 1981b | 1981c | 1981d | 1981e | 1981f | 1981g | 1981h | 1981i | 1981j | 1981k | 1981l | 1981m | 1981n | 1981o | 1981p | 1981q | 1981r | 1981s | 1981t | 1981u | 1981v | 1981w | 1981x | 1981y | 1981z |
| 1982a | 1982b | 1982c | 1982d | 1982e | 1982f | 1982g | 1982h | 1982i | 1982j | 1982k | 1982l | 1982m | 1982n | 1982o | 1982p | 1982q | 1982r | 1982s | 1982t | 1982u | 1982v | 1982w | 1982x | 1982y | 1982z |
| 1983a | 1983b | 1983c | 1983d | 1983e | 1983f | 1983g | 1983h | 1983i | 1983j | 1983k | 1983l | 1983m | 1983n | 1983o | 1983p | 1983q | 1983r | 1983s | 1983t | 1983u | 1983v | 1983w | 1983x | 1983y | 1983z |
| 1984a | 1984b | 1984c | 1984d | 1984e | 1984f | 1984g | 1984h | 1984i | 1984j | 1984k | 1984l | 1984m | 1984n | 1984o | 1984p | 1984q | 1984r | 1984s | 1984t | 1984u | 1984v | 1984w | 1984x | 1984y | 1984z |
| 1985a | 1985b | 1985c | 1985d | 1985e | 1985f | 1985g | 1985h | 1985i | 1985j | 1985k | 1985l | 1985m | 1985n | 1985o | 1985p | 1985q | 1985r | 1985s | 1985t | 1985u | 1985v | 1985w | 1985x | 1985y | 1985z |
| 1986a | 1986b | 1986c | 1986d | 1986e | 1986f | 1986g | 1986h | 1986i | 1986j | 1986k | 1986l | 1986m | 1986n | 1986o | 1986p | 1986q | 1986r | 1986s | 1986t | 1986u | 1986v | 1986w | 1986x | 1986y | 1986z |
| 1987a | 1987b | 1987c | 1987d | 1987e | 1987f | 1987g | 1987h | 1987i | 1987j | 1987k | 1987l | 1987m | 1987n | 1987o | 1987p | 1987q | 1987r | 1987s | 1987t | 1987u | 1987v | 1987w | 1987x | 1987y | 1987z |
| 1988a | 1988b | 1988c | 1988d | 1988e | 1988f | 1988g | 1988h | 1988i | 1988j | 1988k | 1988l | 1988m | 1988n | 1988o | 1988p | 1988q | 1988r | 1988s | 1988t | 1988u | 1988v | 1988w | 1988x | 1988y | 1     |